

Product Information

- 1. What is the difference between TDS-100 and TDS-100S?
- 2. Can the TDS Meter be used to test salt water?

Installation

3. How do I properly install the TDS Meter?


Trouble Shooting

- 4. Is there a recommended interval for calibration?
- 5. Why is the LCD screen not responding?



What is the difference between TDS-100 and TDS-100S?

	Contraction of the Contraction o	
Feature	Titanium One TDS-100	Titanium S1 TDS-100S
Probe Type	Direct plug-in single probe	Remote(wired) single probe
Back Magnet	No magnet on the back	Built-in magnet on the back for mounting



AUTOAQUA

Ö00::

ōōo:

TOAC

000

100



> Can the TDS Meter be used to test salt water?

No

Saltwater aquariums contain a lot of salt and minerals, so the TDS reading will be very high. This meter is designed to measure the quality of RO/DI

water.



AUTOAQUA

000:

000


000



How do I properly install the TDS Meter?

Insert the probe into the ¼" Push-Connect Union Tee, making sure the probe is aligned perpendicular to the Tee

*Please note: When looking directly into the Tee, you should be able to see the two metal pins positioned side by side horizontally.







AUTOAQUA

000:

000

000



Is there a recommended interval for calibration?

The TDS meter is designed for testing RO/DI water.

Since the TDS is only used as needed and RO/DI water is typically clean, it is no need for constant calibration. However, if you feel the TDS is no longer accurate, you can recalibrate it as needed.



000





Why is the LCD screen not responding?

- The battery may be dead.
- The probe may not be installed properly.

If the screen is still not responding after checking the above, please contact us. We'll be happy to assist you as soon as possible.



